

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : B60G 17/005, 17/052, 11/27		A1	(11) International Publication Number: WO 00/53442
			(43) International Publication Date: 14 September 2000 (14.09.00)
(21) International Application Number: PCT/US00/40008 (22) International Filing Date: 22 February 2000 (22.02.00) (30) Priority Data: 60/123,939 12 March 1999 (12.03.99) US (71) Applicant (for all designated States except US): HOLLAND NEWAY INTERNATIONAL, INC. [US/US]; 1950 Industrial Boulevard, P.O. Box 425, Muskegon, MI 49443-0425 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): GALAZIN, Gregory, T. [US/US]; 2566 Meinert Park Road, Montague, MI 49437 (US). THOMAS, Perry, W. [US/US]; 4406 Krystallee Drive, Muskegon, MI 49442 (US). (74) Agent: MCGARRY, John, E.; Rader, Fishman, Grauer & McGarry, an Office of Rader, Fishman & Grauer PLLC, Suite 600, 171 Monroe Avenue, N.W., Grand Rapids, MI 49503 (US).		(81) Designated States: CA, MX, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: TRAILING ARM SUSPENSION WITH ANTI-CREEP AUTOMATIC RESET



(57) Abstract

A trailing arm suspension (10) with a height control valve (70) in combination with an anti-creep device (12) having an automatic reset mechanism (90) that pressurizes the air spring of the trailing arm suspension until the rotatable arm (60) of the anti-creep device (12) is free to rotate from an extended position to a retracted position, even if the ride height is set too low. The automatic reset mechanism (90) adjusts the trailer height to prevent the binding of the trailing arm suspension and the anti-creep device when the height control valve (70) is improperly adjusted.

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **TRAILING ARM SUSPENSION WITH ANTI-CREEP AUTOMATIC RESET**

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

The invention relates to trailing arm suspensions for supporting a vehicle  
5 trailer. In one of its aspects, the invention relates to a trailing arm suspension with an anti-creep device that prevents the translational movement of a parked trailer during loading of the trailer.

#### **Description of the Related Art**

Trailing arm suspensions are commonly used in heavy-duty vehicles such as  
10 tractor/trailers. A typical trailing arm suspension comprises a hanger bracket and an air spring both having one end mounted in spaced relationship and extending downwardly from a frame rail. A trailing arm extends between the hanger bracket and the air spring. One end of the trailing arm is rotatably mounted to the hanger bracket, usually by an elastomeric bushing. The other, opposing, end of the trailing arm is  
15 mounted to a bottom portion or piston of the air spring. The trailing arm is adapted to mount a vehicle axle, which rotatably supports the wheels. Any vertical movement of the wheels in response to changes in the road surface is translated into a rotation of the trailing arm with respect to its pivotal mounting at the hanger bracket. The air spring dampens the pivotal movement of the trailing arm.

20 Tractor-trailer configurations commonly use air-operated brakes that are supplied pressurized air from an air reservoir tank supplied by a compressor on the tractor. The air-operated brakes are well known and include an emergency brake utilizing a large force compression spring that is compressed by the pressurized air to release the emergency brake. The intentional or accidental loss of the pressurized air  
25 to the emergency brakes results in their application. The brakes also include an air-operated service brake for normal braking operations.

The air springs and air-operated brakes are all pressurized by the same air reservoir tank. For safety purposes, the air springs and air-operated brakes are pressurized by discrete plumbing systems or lines to ensure that the brakes are given  
30 priority. The air supply to the air springs is terminated when the pressurized air

-2-

supply drops below a predetermined pressure to ensure a sufficient supply of air to operate the brakes. Within the brake system, the emergency brakes are pressurized by a different line than the service brakes.

It is common for trailers having a trailing arm suspension to incorporate a height control valve to set the ride height of the trailer with respect to the ground. The height control valve is typically connected to the air spring supply line. The height control valve has three positions: a fill position, a neutral position, and an exhaust position. In the fill position, the height control valve fluidly connects the pressurized air source to the air spring to inflate the air spring and raise the frame rail relative to the trailing arm. In the exhaust position, the air spring is fluidly connected to the atmosphere to permit the exhausting of pressurized air from the air spring to deflate the air spring and lower the frame rail relative to the trailing arm. In the neutral position, the air spring is neither connected to the source of pressurized fluid nor to the atmosphere.

The height control valve is actuatable between the filled, neutral, and exhaust positions by a rotatable arm that is mechanically linked by an adjustable mechanism, such as a variable length linkage, to the trailing arm. By adjusting the linkage between the trailing arm and the rotatable arm of the height control valve, it is possible to set the ride height of the trailer to a predetermined level.

In addition to a height control valve, trailers typically include an anti-creep device to prevent the trailer from creeping away from the loading dock as the trailer is being loaded. The creeping phenomenon is attributable to weight that is added to the trailer when the pressurized air source is unavailable, which is typical during loading. Without the availability of additional pressurized air, the air springs cannot be inflated to compensate for the reduced height attributable to the increasing trailer weight during loading. The reduced height is attributed to the relative movement of the frame toward the axle upon the addition of weight to the trailer. The resulting effective pivoting of the frame with respect to the rotates the wheels since the wheels are in contact with the ground, which drives the trailer away from the loading dock. This is known as the creeping phenomenon.

-3-

One type of class of anti-creep devices comprises a rotatable arm that is coupled to an air actuator controlled by supplied air by the air spring system and actuated by the brake system. When the vehicle is operated under normal conditions, the rotatable arm is kept in a raised position generally parallel and beneath the frame rail. When the trailer is being loaded and the emergency brakes are exhausted, the rotatable arm is rotated to an extended position where its end lies just above the trailing arm. Any relative movement of the frame rail and the trailing arm will be stopped once the rotatable arm contacts the trailing arm.

The rotatable arm anti-creep devices have known disadvantages. First, if the trailer, especially a loaded trailer, is unhooked from the tractor and allowed to sit for an extended period of time, the height control valve can temporarily "freeze" prohibiting the introduction of pressurized air from the trailer's air reservoir tank to the air springs to raise the trailer to its predetermined ride height. This problem is exacerbated in that over extended periods of time, the pressurized air will slowly leak from the pressurized air system resulting in a very slow and gradual lowering of the vehicle ride height. When one or both of these conditions occur, the arms of the anti-creep device, which are in the extended position, can be bound or compressively retained in the extended position.

The coupling of the tractor to the trailer and the corresponding pressurization of the air systems will not always overcome the temporary freezing of the height control valve, leaving the suspension in an inoperable state. The subsequent jarring of the trailer during initial movement will free the frozen height control valve and the height control valve can operate normally to raise the trailer and free the arms. If the height control valve remains frozen, the suspension will not function properly and can be damaged. Second, during the backing of the trailer toward the dock, it is common for the tractor operator to quickly and forcefully apply the brakes when the trailer has reached the loading position relative to the dock and simultaneously apply the emergency brake, which immediately moves the arms of the anti-creep device to the extended position. Depending on the timing between stopping the rearward movement of the trailer and the application of the emergency brakes, it is possible for the momentum of the trailer to temporarily lower the rear of the trailer relative to the

-4-

trailing arm, preventing the full extension of the rotatable arm of the anti-creep device. Alternatively, it is possible for the rotatable arm of the anti-creep device to be fully deployed but the rearward momentum of the trailer lowers the height of the trailer and compresses the arm between the trailer frame and the trailing arm. If the trailer air  
5 reservoir tank is not pressurized above the safety threshold, then no air is available to raise the trailer to the preferred height.

It is desirable to prevent the binding of the anti-creep device arms between the trailer frame and the trailing arm to avoid damaging the suspension.

#### SUMMARY OF THE INVENTION

10 The invention addresses the shortcoming of the prior art in a trailing arm suspension with a height control valve in combination with an anti-creep device by means of an automatic reset mechanism that pressurizes the air spring until the rotatable arm is free to rotate to the retracted position, even if the ride height is set too low. The automatic reset mechanism adjusts the trailer height to prevent the binding  
15 of the trailing arm suspension and the anti-creep device when the height control valve is improperly adjusted.

According to the invention, a trailing arm suspension for supporting ground-engaging wheels relative to a vehicle frame has a trailing arm with a forward portion adapted to be mounted to the vehicle frame for pivotable movement with respect  
20 thereto. An air spring is mounted at one end to the trailing arm and is adapted to be mounted at another end to the vehicle frame. An axle is connected to the trailing arm for carrying the ground-engaging wheels. A pneumatic air supply system for pressurizing the air spring includes a height control valve for controlling the introduction of exhaustion of pressurized air to and from the air spring to control the  
25 relative position of the vehicle frame with respect to the axle. An anti-creep mechanism is adapted to be mounted to the vehicle frame and is movable between a retracted position where the trailing arm is free to pivot relative to the vehicle frame and an extended position where the trailing arm is substantially prevented from pivoting toward the vehicle frame. An auxiliary air supply system for pressurizing the  
30 air spring includes a second control valve for controlling the pressure to the air spring. An actuator is responsive to the movement of the anti-creep mechanism between the

-5-

extended and retracted positions for closing the second control valve when the anti-creep mechanism is in the retracted position and is further responsive to movement of the anti-creep mechanism between the retracted and extended positions for opening the second control valve.

5           In a preferred embodiment, the arm is adapted to be pivotally mounted to the vehicle frame and the arm extends between the vehicle frame and the trailing arm to block the relative pivotable movement of the trailing arm toward the frame. The actuator preferably comprises a link coupling the arm to the second control valve. When the arm is the retracted position, the link closes the control valve to prevent  
10           pressurization of the air spring. When the arm is in the extended position, the link opens the control valve for pressurization of the air spring from the auxiliary air supply.

          In a preferred embodiment, the control valve comprises a body having an inlet port fluidly connected to the auxiliary air supply system, an outlet port fluidly  
15           connected to the air spring and a lever movable between a first position at which the inlet and outlet ports are fluidly blocked and a second position at which the inlet and outlet ports are fluidly connected. The link is connected to the lever and moves the lever between the first and second positions as the arm is moved between the retracted and extended positions.

20           In a further embodiment of the invention, the anti-creep mechanism further comprises a rod adapted to be mounted for rotation about an elongated axis thereof to the vehicle frame and the arm is fixedly mounted to the rod whereby rotation of the rod about its longitudinal axis moves the arm between the retracted and extended positions.

25           The anti-creep mechanism further comprises in a preferred embodiment an air-operated actuator connected to the rod and fluidly connected to the pneumatic air supply system. The pneumatic air supply system pressurizes the air-operated actuator to rotate the rod to a retracted position and thereby rotate the arm to the retracted position. When the pneumatic air supply system is shut down, the rod rotates to an  
30           extended position at which the arm is rotated to the extended position.

-6-

### BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a combination perspective and schematic view illustrating the pressurized air system for the suspension, anti-creep device, and height control device;

5        FIG. 2 is a perspective view of the air-operated elements of the trailing arm suspension of FIG. 1; and

FIG. 3 is a schematic illustration of the air control system of FIG. 1.

### DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 illustrates a trailing arm suspension 10 in combination with an anti-  
10        creep device 12 and a height control device 14. The trailing arm suspension 10 is mounted to a longitudinal frame rail 16 and supports an axle 18 to which wheels 20 are mounted on opposite ends of the axle 18. In a typical trailer application, two pairs of trailing arm suspensions are used to mount the axle 18 to the frame rail 16 and support opposing ends of the axle 18. Only one of the trailing arm suspensions will  
15        be described in detail.

The trailing arm suspension 10 comprises a hanger bracket 22 fixedly mounted to the frame rail and to which is rotatably mounted a trailing arm 24 by means of a bushed connection 26 located at the forward end of the trailing arm 24. The rearward end of the trailing arm 24 mounts an air spring 30 at a lower end thereof, which is  
20        connected to the frame rail 14 at its upper end. The air spring 30 resiliently resists upward movement of the trailing arm 24 with respect to the frame and comprises an air bag 32 mounted to the frame rail 14 and a piston 34 mounted to a platform 36 on the trailing edge of the trailing arm 24. As the trailing arm 24 rotates, the piston 34 is urged into the air bag 32 to resiliently resist movement of the trailing arm 24 toward  
25        the frame rail 14.

The axle 16 is mounted to the trailing arm 24 by an axle mounting bracket 40 connected to the trailing arm 24 through two bushed connections 44 and 46. A shock absorber 48 can be mounted between the frame rail 14 and the axle bracket 40 to dampen the movement of the trailing arm 24 with respect to the frame.

30        Referring to FIGS. 1 and 2, the anti-creep device 12 comprises an air-operated actuator 50 mounted to a crossbeam (not shown) extending between the parallel frame



-7-

rails 16. The actuator 50 comprises a reciprocating shaft 52 that terminates in a clevis 54. The reciprocating shaft moves between a retracted position and an extended position.

5 The actuator 50 is well known and does not require additional description. For the invention, it is only important to note that when pressurized air is supplied to the actuator 50, the shaft 52 is in the retracted position and when the actuator 50 is not supplied pressurized air, the shaft 52 is in the extended position.

10 A rod 58 spans the frame rails 16 and has a cam 56 that is rotatably pinned to the clevis 54. The rod 58 has opposing ends, each of which is disposed below the corresponding frame rail 16 and is pivotally mounted thereto. A stop arm 60 is welded to each end of the rod 58 and is movable between a retracted position (shown in phantom) and an extended position. The stop arm 60 is in the retracted position when the shaft 52 is in the extended position. Similarly, the stop arm 60 is in the extended (down) position when the shaft 52 is in the retracted position. Thus, when  
15 pressurized air is exhausted from the actuator, the arm is in the extended position.

When the stop arm 60 is in the retracted position, the trailing arm 24 is free to rotate relative to the frame 16. When the stop arm 60 is in the extended position, the trailing arm 24 can rotate only a short distance until it contacts the stop arm which thereby prevents further relative movement of the frame rail 16 with respect to the  
20 trailing arm 24.

The stop arm 60 is moved between the retracted and extended positions by the introduction and exhaustion, respectively, of pressurized air into and from the actuator 50 from an air reservoir tank 62, which is generally a compressor associated with the tractor. The compressor supplies pressurized air to the tractor/trailer through two  
25 separate systems known as the brake air system and the air spring system. The brake air system is divided into an emergency brake line and a service brake line. The compressor supplies pressurized air to an air reservoir tank 62, which is directly connected to the brake air system and connected through a pilot valve 64 and a pressure protection valve (PPV) 84 to the spring air system. The pilot valve 64  
30 permits the flow of pressurized air to the spring air system only when the emergency brake line is pressurized. The release of the emergency brakes, which also function as

-8-

the parking brakes, disconnects the pilot valve from the air supply. The PPV 84 fluidly connects the air reservoir tank 62 to the spring air system only when the pressure in the tank exceeds a predetermined pressure, typically about 70 psig.

The pilot valve 64 supplies air to the spring air system when the vehicle is under normal operation, i.e., the emergency brakes are not applied. The PPV 84 supplies pressurized air to the spring air system as required until the air reservoir tank drops below the threshold pressure. Generally, the tank will have sufficient pressure to supply the brake air system for a short time after the tractor's compressor is shut off or the emergency brakes are applied.

The pilot valve 64 has a normally closed port 66, a cylinder or common port 82, and a normally open exhaust port 104. The normally open and closed positions of the various pilot valve ports refer to the status of the ports when there is no pressurized air being supplied to the pilot valve 64 from the emergency brake line. When pressurized air is supplied to the pilot valve 64 from the emergency brake line, the cylinder port 82 is fluidly connected to the normally closed port 66 permitting fluid flow from the air reservoir tank 62 through the pilot valve 64 to the anti-creep device 12. When no pressurized air is supplied to the pilot valve 64, the ports 66, 82 are closed relative to each other, and the port 82 opens relative to the exhaust port 104, shutting off the air supply to the anti-creep device and opening the cylinder port 82 to the exhaust port 104.

When the anti-creep device 12 is supplied pressurized air by the pilot valve 64, pressurized air is supplied through the pilot valve 64 to the brake actuator valve 50 to maintain the reciprocating shaft 52 in the extended position and the stop arm 60 in the retracted position. When the pressurized air to the anti-creep device is shut off, the normally closed cylinder port 66 will close and air from the brake actuator 50 will pass through port 82 and exhaust through port 104. A spring in the brake actuator 50 causes the shaft 58 to rotate and move the arm 60 to the extended position.

A height control valve 70 is preferably mounted to the frame rail 16 and comprises an air supply port 72, air spring port 74, and exhaust port 76. The height control valve 70 further includes a pivotally mounted lever 78 to control the flow between the various ports 72, 74, 76. One end of the pivotally mounted lever 78 is

-9-

connected to an upper end of an adjustable link 80, whose lower end is connected to the trailing arm 24. Thus, the relative movement of the frame rail 16 and trailing arm 24 will move the link 80, which will move the lever 78.

5 The lever 78 is movable between three operational positions: a fill position where the air supply port 72 is fluidly connected to the air spring port 74; a neutral position where none of the air supply port 72, air spring port 74, and exhaust port 76 are in fluid communication; and an exhaust position where the air spring port 74 is in fluid communication with the exhaust port 76.

10 The air supply port 72 is fluidly open to the normally closed port 66 of the pilot valve 64 and a pressure protection valve (PPV) 84. Both the pilot valve 64 and PPV 84 are supplied by the air supply 62. When the air supply 62 supplies air through the PPV 84, air is supplied to the air supply port 72 of the height control valve 14. When there is no air supply through the pilot valve 64, the PPV 84, no air is supplied to the height control valve 70. The height control valve is supplied air only as long as  
15 the pressure in the air reservoir tank 62 remains above the threshold pressure.

An automatic reset device 90 is provided to add pressurized air to the air springs 30 while the stop arm 60 is in the extended position, regardless of the ride height of the vehicle. The automatic reset device 90 comprises a sensor valve 91 having an inlet port 94, an air spring port 96, and an exhaust port 97. The inlet port 94  
20 is fluidly connected to the cylinder port 82 of the pilot valve 64 so that pressurized air is supplied to the sensor valve 91 when the emergency brake line is pressurized. The air spring port 96 is connected to the air springs 30 through a check valve 106. The exhaust port 76 of the height control valve 70 connects to the output of the neutral port 96 below the check valve 106.

25 The sensor valve 91 further comprises a lever 98 that is operable between three positions. In the first or fill position, fluid flow is permitted between the inlet port 94 and the air spring port 96. In the second or neutral position, none of the ports 94, 96, and 97 are fluidly connected. In the third or exhaust position, the inlet port 94 is fluidly connected to the exhaust port 97. The lever 98 is operably connected to the  
30 rod 58 by a link 100 that extends from the lever 98 and is connected to a bracket 102 mounted on the rod 58.

-10-

The mechanical linkage between the rod 58 of the anti-creep device and the lever 98 of the automatic reset device couples the actuation of the valve 92 with the position of the stop arms 60 of the anti-creep device. For example, when the stop arms 60 are in the retracted position, the rod 58 will rotate to a position in which the lever 98 is moved to the exhaust position, blocking fluid communication between the inlet port 94 and the air spring port 96 to thereby block the flow of pressurized air from the air reservoir tank 62 to the air spring 30. When the stop arms 60 are in the extended position, the lever 98 is in the fill position in which the inlet port 94 and air spring port 96 are in fluid communication so that pressurized air can pass from the air reservoir tank 62 to the air springs 30, assuming the air supply is pressurized above the PPV 84 threshold.

The operation of the anti-creep device and automatic reset will now be described. Initially, a general description of the operation should prove beneficial to a more complete understanding. The air reservoir tank 62 supplies all of the pressurized air to the actuator 50, height control valve 70, and sensor valve 90. All of the air leaving the air reservoir tank 62 is directed through the pressure protection valve 84. No air can be supplied from the air reservoir tank 62 to the actuator 50, height control valve 70, and sensor valve 90, if the air pressure in the air reservoir tank 62 drops below the threshold value for the pressure protection valve 84.

The pilot valve 64 is supplied pressurized air from the air reservoir tank 62 through the pressure protection valve 84. The pilot valve 64 controls the flow of pressurized air from the air reservoir tank 62 to the sensor valve 90 and the actuator 50. If the emergency brakes are not applied, the pilot valve 64 fluidly connects the air from the air reservoir tank 62 to the actuator 50 and the sensor valve 90. If the emergency brakes are applied, the pilot valve disconnects the actuator 50 and sensor valve 90 from the pressurized air of the air reservoir tank 62 and exhausts the actuator 50 and sensor valve 90 to the atmosphere. If pressurized air supplied to the actuator 50 and the sensor valve 90, the emergency brakes cannot be applied and the pressurized air will tend to urge the arm 60 upwardly to the retracted position and the sensor valve 91 will fill the air springs 30 until the arm 60 is in the retracted position.

-11-

It is important to note that regardless of the status of the emergency brakes, the air reservoir tank 62 continuously supplies pressurized air to the height control valve 70 as long as the pressure in the air reservoir tank 62 exceeds the threshold pressure of the pressure protection valve 84. The exhaust of the height control valve 70 is fluidly  
5 connected to the air springs 30.

Looking at a typical operation scenario, as the trailer is being moved into a loading position, the arm 60 is in the retracted position, and the air reservoir tank 62 supplies pressurized air to the pilot valve 64 through the PPV 84 and the emergency brake line is pressurized. In this condition, the normally closed valves 66 and 82 to  
10 each other and the air supply to thereby supply pressurized air to the brake actuator 50, height control valve 70, and the automatic reset device 90. The normally open exhaust port 104 is closed. With pressurized air being supplied to the brake actuator 50, the reciprocating shaft 52 is extended to thereby maintain the stop arms 60 of the anti-creep device in their retracted position. With pressurized air supplied to the  
15 height control valve 70, the height control valve is free to maintain the ride height of the vehicle at the predetermined height as set by the adjustable link 80. With the pressurized air supplied to the automatic reset device 12, and the stop arms 60 being in the retracted position, the lever 98 of the reset valve 92 is maintained in the neutral position to prevent the flow of pressurized air from the vehicle air supply into the air  
20 springs 30.

Once the trailer is moved to the desired location for loading, the parking brakes are applied, exhausting the emergency brake line, which closes the port preventing the flow of pressurized air from the air reservoir tank 62 to the actuator 50 and sensor valve 90, and opens the exhaust port 104 to fluidly connect the actuator 50  
25 and sensor valve 90 to atmosphere for exhausting. As the air is exhausted from the actuator 50 through the normally open port 104 of the pilot valve 64, the reciprocating shaft 52 is retracted to thereby rotate the rod 58 to move the stop arms 60 from their retracted position to their extended position and to fluidly connect ports 94, 96 of the sensor valve 91. With the stop arms 60 of the anti-creep device in their extended  
30 position, the trailer is now ready for loading.

-12-

In the parked position with the emergency brake line exhausted, the height control valve 70 is still connected to the air supply 62 through the PPV 84. If the lever 78 is in the fill position, ports 72 and 74 are fluidly connected and air springs 30 will take on air until the valve 70 is satisfied. If the valve 70 is in the neutral position, no air flow occurs to the air springs. If the valve 70 is in the exhaust position, ports 74 and 76 are fluidly connected, resulting in air being exhausted from the air springs 30 as it flows through ports 74, 76 to port 96, which is open to port 94, which is open to port 82, where it is exhausted out of exhaust port 104. If for some reason the arms 60 cannot be rotated to the extended position when the emergency brakes are applied (for example, no air from the supply 62 to pilot valve 64), the ports 96, 97 will be open to each other, instead of 94, 96, and the air springs 30 will exhaust through port 97, instead of 104.

As the trailer is loaded, the additional weight added to the trailer results in the relative movement of the frame rails 16 toward the trailing arm 24. The height control valve 70 will continue to supply pressurized air to the air springs 30 until the pressure in the air reservoir tank 62 drops below the threshold. Upon continued loading, the relative movement will continue between the frame rails 16 and the trailing arm 24 until the stop arms 60 abut the trailing arms to thereby prohibit further relative movement of the frame rail 16 and trailing arm 24. Once the loading is completed, the trailer is prepared to be moved away from the loading position by the vehicle. The compressor on the tractor begins pressurizing the air reservoir tank 62 and pressurizes the emergency brake line. Upon the release of the parking brakes, the emergency brake line applies pressure to the pilot port, resulting in the opening of the normally closed valves 66 and 82 to each other and to the air reservoir tank 62 to supply pressurized air to the actuator 50, height control valve 70, and automatic reset device 90.

As the actuator 50 is pressurized, the arms 60 are initially in the extended position and the sensor valve 90 is in the fill position. If the arms 60 are trapped in the extended position because of the compressive force acting on the arms from the frame 16 and suspension 10, the sensor valve remains in the fill position and pressurized air passes through the open ports 94 and 96 to the air springs 30,

-13-

regardless of the position of the lever 78 of the height control valve 70. The pressurized air will continue to flow from the sensor and valve to the air springs through the check valve 106 until the air springs 30 are inflated a sufficient amount to free the arms so that the actuator 50 can move the rod 58 and thereby move the arms 60 to their retracted position.

If the height control valve 70 is properly adjusted, it is most likely that the lever 78 will be in the fill position after loading and the ports 72, 74 will be open to each other because of the relative movement of the frame 16 toward the suspension 10 caused by the loading of the trailer. If the ports 72, 74 are open to each other, then pressurized air will be supplied to the air springs 30 through the height control valve 70 in addition to the pressurized air supplied by the reset device 90.

If the height control valve 70 is not properly adjusted and the arms 60 are stuck in their extended position, the height control valve 70 could be in either the neutral position or the exhaust position. In the neutral position, no air flow can pass through the height control valve 70. In the exhaust position, the ports 74, 76 are connected and pressurized air will be supplied to the air springs 30. Once the arms 60 have been rotated to the retracted position after the removal of the parking brake, the lever 98 of the valve 91 is rotated downwardly in response to the rotation of the rod 58 as the arms move to the retracted position and port 96 and 97 are then open to each other. In this position, no air can flow from the air springs through the check valve 106 back to either port 96 of the reset device 90 or port 76 of the height control valve 70. If the height control valve 70 is in the bypass position (ports 74 and 76 are open to each other), the pressurized air in the air springs 30 will exhaust to the atmosphere through port 96 and 97. If the ride height is too low, the height control valve 70 will be in the fill position (ports 72 and 74 are open to each other) and pressurized air will be supplied to the air springs 30.

From this point on, the height control valve 14 will solely control the addition and exhaustion of pressurized air from the air springs 30, until the next loading sequence.

The invention advantageously addresses the undesirable situation of the binding of the trailing arm suspension and the stop arms because the predetermined

-14-

ride height is improperly set. The automatic reset device 90 permits the addition of pressurized air into the air springs 30 until the stop arms are retracted and then returns control to the height control valve for the continuation of normal operations.

Reasonable variation and modification are possible within the scope of the  
5 foregoing disclosure and claims without departing from the spirit of the invention  
which is defined in the appended claims.



## CLAIMS

1. A trailing arm suspension for supporting ground engaging wheels relative to a vehicle frame, the trailing arm suspension comprising:
  - a trailing arm having a forward portion adapted to be mounted to the vehicle frame for pivotal movement with respect thereto;
  - 5 an air spring mounted at one end to the trailing arm and adapted to be mounted at another end to the vehicle frame;
  - an axle connected to the trailing arm for carrying the ground engaging wheels;
  - a pneumatic air supply system for pressurizing the air spring and
  - 10 including a height control valve for controlling the introduction and exhaustion of pressurized air to and from the air spring to control the relative position of the vehicle frame with respect to the axle;
  - an anti-creep mechanism adapted to be mounted to the vehicle frame and movable between a retracted position where the trailing arm is free to pivot
  - 15 relative to the vehicle frame and an extended position where the trailing arm is substantially prevented from pivoting toward the vehicle frame;
  - an auxiliary air supply system for pressurizing the air spring and including a second control valve for controlling the pressure to the air spring; and
  - an actuator responsive to the movement of the anti-creep mechanism
  - 20 between the extended and retracted positions for closing the second control valve when the anti-creep mechanism is in the retracted position and for opening the second control valve when the anti-creep mechanism is in the extended position.
2. The suspension according to claim 1 wherein the anti-creep mechanism comprises an arm adapted to be pivotally mounted to the vehicle frame; and wherein the arm extends between the vehicle frame and the trailing arm to block the relative pivotal movement of the trailing arm toward the frame.
3. The suspension according to claim 2 wherein the actuator comprises a link coupling the arm to the second control valve wherein when the arm is in the retracted position, the link closes the control valve to prevent pressurization of the air

-16-

spring; and when the arm is in the extended position, the link opens the control valve  
5 for pressurization of the air spring.

4. The suspension according to claim 3 wherein the control valve comprises a body having an inlet port fluidly connected to the auxiliary air supply system, an outlet port fluidly connected to the air spring, and a lever movable between a first position where the inlet and outlet ports are fluidly blocked and a second  
5 position where the inlet and outlet ports are fluidly connected, and the link is connected to lever and moves the lever between the first and second positions as the arm is moved between the retracted and extended positions.

5. The suspension according to claim 4 wherein the anti-creep mechanism further comprises a rod adapted to be rotatably mounted to the vehicle frame and the arm is fixedly mounted to the rod whereby rotation of the rod moves the arm between the retracted and extended positions.

6. The suspension according to claim 5 wherein the anti-creep mechanism further comprises an air-operated actuator connected to the rod and fluidly connected to the pneumatic air supply system, wherein when the pneumatic air supply system pressurizes the air-operated actuator, the rod is rotated to a retracted position where  
5 the arm is in the retracted position, and when the pressurized air to the air-operated actuator is exhausted, the rod is rotated to an extended position where the arm is in the extended position.

7. The suspension according to claim 6, and further comprising a source of pressurized air, a pilot valve fluidly connecting the source of pressurized air to the pneumatic air supply system and the auxiliary air supply system, and the pilot valve supplies pressurized air to the auxiliary supply system when the arm is in the extended  
5 position.

8. An anti-creep system for a trailing arm suspension comprising a trailing arm having a front portion mounted to a vehicle frame for pivotal movement with respect thereto, an air spring mounted at one end to the trailing arm and adapted

-17-

to be mounted to the vehicle frame at another end, an axle connected to the trailing  
5 arm for carrying ground engaging wheels, and a pneumatic air supply system for  
pressurizing the air spring and including a height control valve for controlling the  
introduction and exhaustion of pressurized air to and from the air spring to control the  
relative position of the axle with respect to the vehicle frame, the anti-creep system  
comprising:

10 an anti-creep mechanism adapted to be mounted to the frame and  
movable between a retracted position where the trailing arm is free to pivot relative to  
the vehicle frame and an extended position where the trailing arm is substantially  
prevented from pivotal movement toward the vehicle frame;

an auxiliary air supply system for pressurizing the air spring, including  
15 a second control valve for controlling the pressure supplied to the air spring; and  
an actuator responsive to the movement of the anti-creep mechanism  
between the extended and retracted positions for closing the second control valve  
when the anti-creep mechanism is in the retracted position.

9. The anti-creep system according to claim 8 wherein the anti-creep  
mechanism comprises an arm adapted to be pivotally mounted to the vehicle frame;  
and when the anti-creep mechanism is in the extended position, the arm extends  
between the vehicle frame and the trailer to block the relative pivotal movement of the  
5 trailing arm toward the frame.

10. The anti-creep system according to claim 9 wherein the actuator  
comprises a link coupling the arm to the second control valve wherein when the arm  
is in the retracted position, the link closes the second control valve to prevent the flow  
of pressurized air from the auxiliary air supply system to the air spring, and when the  
5 arm is in the extended position, the link opens the control valve to permit the flow of  
pressurized air from the auxiliary air supply to the air spring.

11. The anti-creep system according to claim 10 wherein the control valve  
comprises a body having an inlet port fluidly connected to the auxiliary air supply  
system, an outlet port fluidly connected to the air spring, and a lever movable between

-18-

a first position where the inlet and outlet ports are fluidly separated and a second  
5 position where the inlet and outlet ports are fluidly connected, and the link is  
connected to lever and moves the lever between the first and second positions as the  
arm is moved between the retracted and extended positions.

12. The anti-creep system according to claim 11 wherein the anti-creep  
mechanism further comprises a rod adapted to be rotatably mounted to the vehicle  
frame and the arm is fixedly mounted to the rod whereby rotation of the rod moves the  
arm between the retracted and extended positions.

13. The suspension according to claim 12 wherein the anti-creep  
mechanism further comprises an air-operated actuator connected to the rod and fluidly  
connected to the pneumatic air supply system, wherein when the pneumatic air supply  
system pressurizes the air-operated actuator, the rod is rotated to a retracted position  
5 where the arm is in the retracted position, and when the pneumatic air supply system  
does not pressurize the air-operated actuator, the rod is rotated to an extended position  
where the arm is in the extended position.

14. A trailing arm suspension for controlling the movement of ground  
engaging wheels relative to a vehicle frame, the trailing arm suspension comprising:  
a trailing arm having a forward portion adapted to be mounted to the  
vehicle frame for pivotal movement thereto;  
5 an air spring mounted at one end to the trailing arm and adapted to be  
mounted at another end to the vehicle frame;  
an axle connected to the trailing arm for carrying the ground engaging  
wheels;  
a pneumatic air supply system for pressurizing the air spring and  
10 operable between a pressurized state and a non-pressurized state;  
a height control valve fluidly connecting the pneumatic air supply to  
the air spring for controlling the introduction and exhaustion of pressurized air to and  
from the air spring to control the relative position of the axle with respect to the  
vehicle frame;

15                    an air-operated anti-creep mechanism fluidly connected to the  
pneumatic air supply system and adapted to be mounted to the vehicle frame and  
movable between a retracted position where the axle is free to move relative to the  
vehicle frame and an extended position where the axle is substantially prevented from  
moving relative to the vehicle frame;

20                    a second control valve fluidly connecting the pneumatic system and the  
air spring and responsive to the movement of the anti-creep mechanism between the  
extended and retracted positions for opening the control valve to provide pressurized  
air to the air spring when the anti-creep mechanism is in the extended position.

15.        The suspension according to claim 14 wherein the anti-creep  
mechanism comprises an arm adapted to be pivotally mounted to the vehicle frame;  
and, the arm extends between the vehicle frame and the trailer to block the relative  
pivotal movement of the trailing arm toward the frame when the anti-creep  
5        mechanism is in the extended position.

16.        The suspension according to claim 15 wherein the anti-creep  
mechanism further comprises a rod adapted to be rotatably mounted to the vehicle  
frame and the arm is fixedly mounted to the rod, whereby rotation of the rod moves  
the arm between the retracted and extended positions.

17.        The suspension according to claim 16 wherein the anti-creep  
mechanism further comprises an air-operated actuator connected to the rod and fluidly  
connected to the pneumatic air supply system, wherein when the pneumatic air supply  
system pressurizes the air-operated actuator, the rod is rotated to a retracted position,  
5        and the rod is rotated to an extended position when the pneumatic air supply system  
does not supply pressurized air to the air-operated actuator.


18.        The suspension according to claim 14 and further comprising an  
actuator responsive to the movement of the anti-creep mechanism for opening the  
control valve when the anti-creep mechanism is in the extended position.

-20-

19. The suspension according to claim 18 wherein the actuator comprises a link coupling the arm to the control valve wherein when the arm is in the retracted position, the link closes the control valve preventing the flow of pressurized air from the auxiliary air supply system to the air spring, and when the arm is in the extended position, the link opens the control valve permitting the flow of pressurized air from the auxiliary air supply to the air spring.

20. The suspension according to claim 19 wherein the control valve comprises a body having an inlet port fluidly connected to the auxiliary air supply system, an outlet port fluidly connected to the air spring, and a lever movable between a first position where the inlet and outlet ports are not fluidly connected and a second position where the inlet and outlet ports are fluidly connected, and the link is connected to lever and moves the lever between the first and second positions as the arm is moved between the retracted and extended positions.

**1/3**



**Fig. 1**

2/3




Fig. 2



3/3




Fig. 3

# INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/40008

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60G17/005 B60G17/052 B60G11/27

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 37864 A (GALAZIN GREGORY T ; NAI NEWAY INC (US)) 16 October 1997 (1997-10-16) page 10, line 19 -page 11, line 19; figures	1,2,5-9, 11-18
A	US 4 865 349 A (CHURCH JR WILLIAM P) 12 September 1989 (1989-09-12) abstract; figures	1,8,14
A	WO 93 19959 A (DRIVERITE LIMITED ; NASH HAROLD (IE); RONAN BRENDAN (IE); CARSON PA) 14 October 1993 (1993-10-14) abstract; figures 1,3-5	
A	EP 0 401 100 A (EUROP SEMI REMORQUES) 5 December 1990 (1990-12-05) abstract; figures	
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 June 2000

Date of mailing of the international search report

05/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Tsitsilonis, L

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/40008

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 96 09179 A (NAI NEWAY INC ; RICHARDSON  GREGORY A (US); HAGAN LYLE M (US))  28 March 1996 (1996-03-28)  abstract; figures</p> <p>-----</p>	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International publication No

PCT/US 00/40008

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 9737864 A	16-10-1997	AU 2663897 A CA 2250144 A EP 0891264 A	29-10-1997 16-10-1997 20-01-1999
US 4865349 A	12-09-1989	CA 1299206 A	21-04-1992
W0 9319959 A	14-10-1993	AT 166621 T AU 3766493 A DE 9390073 U DE 69318832 D DE 69318832 T EP 0633849 A IE 73659 B	15-06-1998 08-11-1993 03-02-1994 02-07-1998 03-12-1998 18-01-1995 18-06-1997
EP 0401100 A	05-12-1990	FR 2648759 A NO 902376 A PT 94180 A SE 9001859 A	28-12-1990 03-12-1990 31-12-1991 01-12-1990
W0 9609179 A	28-03-1996	AU 1253295 A	09-04-1996